

1 PH AUTO TRANSFORMER

Sr.No	VA	Length	Width	Height	X	Y	Weight(KGS)
1	25	56	50	110	46	0	1
2	50	75	85	125	55	65	1.8
3	75	100	75	130	75	55	2.1
4	100	100	90	130	75	67	2.8
5	125	100	90	130	75	67	2.8
6	150	130	85	155	100	67	3.5
7	200	130	85	155	100	71	3.95
8	250	130	95	155	100	77	4.6
9	300	140	95	175	110	64	4.5
10	400	140	110	175	110	77	5.8
11	450	140	115	175	110	84	6.4
12	500	150	110	195	120	85	8
13	550	150	110	195	120	85	8.35
14	600	150	110	195	120	91	9.2
15	650	150	115	195	120	98	10.2
16	700	150	115	195	120	98	10.2
17	750	150	120	195	120	104	11.1
18	800	150	120	195	120	104	11.1
19	1000	150	130	195	120	110	12.1
20	1250	200	130	220	150	80	14.9
21	1500	200	140	220	150	92	17.4
22	1750	200	150	220	150	105	19.9
23	2000	230	120	230	200	96	17.9
24	2500	230	140	230	200	109	21.4
25	3000	230	140	230	200	115	23.2
26	3500	250	150	270	190	110	28.4
27	4000	250	170	280	190	124	32.5
28	4500	250	170	280	190	129	35.1
29	5000	250	180	280	190	136	37.5

Note:- Use This Formula to select your require Auto Transformer.

Dimensional KVA =	Required KVA x	$\frac{(\text{highest voltage}) - (\text{lowest voltage})}{(\text{highest voltage})}$
-------------------	----------------	---

Always specify the Required KVA, highest voltage & lowest voltage rating in your order!